

DIRECT FET® AMPLIFIER FDS 1.350

Ultra-compact mono amplifier

- Aluminium chassis
high heat dissipation



- Hidden connectors
Stackable chassis
Built-in active crossovers

- D Class amplification
Optimal integration Direct FET® Technology

KEY POINTS

- D Class – Direct Fet® Technology - Efficient heat dissipation and precision
- Stable under 2 Ohms
- Stackable aluminium chassis with high heat dissipation
- Low noise operational amplifiers New Japan Radio® NJM4580
- Low ESR capacitors - 105°C (220°F)
- Pseudo-balanced inputs



TECHNICAL SPECIFICATIONS

Mono D Class amplifier with dual output
CEA power (4 Ohms): 1x210 Watts RMS
Power max (2 Ohms): 1x350 Watts RMS

Low-pass crossover: 40Hz-400Hz
Progressive phase adjustment (0-180°)
Bass boost (0/6dB/12dB)
Protections: Short circuit / low impedance / Polarity reversal / DC / power drop / heat protection

Dimensions (LxHxW):
7¹³/₁₆ x 4¹/₄ x 1¹¹/₁₆ [199x108x43mm]
Weight: 1.9 lbs

 **Performance**
CREATE YOUR SOUND

 **FOCAL**®
THE SPIRIT OF SOUND