

# DIRECT FET® AMPLIFIER FDS 4.350

Ultra-compact 4-channel amplifier

- Aluminium chassis  
high heat dissipation



- Hidden connectors  
Stackable chassis  
Built-in active crossovers

- D Class amplification  
Optimal integration of Direct FET® Technology

## KEY POINTS

- D Class – Direct Fet® Technology - Efficient heat dissipation and precision
- Stable under 2 Ohms
- Stackable aluminium chassis with high heat dissipation
- Low noise operational amplifiers New Japan Radio® NJM4580
- Low ESR capacitors - 105°C (220°F)
- Pseudo-balanced inputs



## TECHNICAL SPECIFICATIONS

**4/3/2-channel D Class amplifier**

**CEA power (4 Ohms):** 4x58 Watts RMS

**Power max (2 Ohms):** 4x100 Watts RMS

**Power max (4 Ohms bridged):** 2x200 Watts RMS

**Configurable high-pass/low-pass crossover:** 40Hz-400Hz

**Full range mode**

**Protections:** Short circuit / low impedance / polarity reversal / DC / power drop / heat protection

**Dimensions (L x H x W):**

7<sup>13</sup>/<sub>16</sub> x 4<sup>1</sup>/<sub>4</sub> x 1<sup>11</sup>/<sub>16</sub> [199x108x43mm]

**Weight:** 1.9 lbs

 **Performance**  
CREATE YOUR SOUND

 **FOCAL**®  
THE SPIRIT OF SOUND